



DASH series

DASH series

SURFACE DOWNLIGHT



BRIDGE LUX 50,000hrs | 8W | 3000K 4000K 5000K | 15° 24° 36° | Fixed | Ra >90 | UGR <19 | IP20 | 3 | CE

Light Source	Power	Voltage	CCT	Beam Angle	Code
COB LED	8W	AC220-240V	3000K	15°	DL-7381-08-3015-P-C
				24°	DL-7381-08-3024-P-C
				36°	DL-7381-08-3036-P-C
COB LED	8W	AC220-240V	4000K	15°	DL-7381-08-4015-P-C
				24°	DL-7381-08-4024-P-C
				36°	DL-7381-08-4036-P-C
COB LED	8W	AC220-240V	5000K	15°	DL-7381-08-5015-P-C
				24°	DL-7381-08-5024-P-C
				36°	DL-7381-08-5036-P-C
COB LED	8W	AC220-240V	3000K	15°	DL-7381S1-08-3015-P-C
				24°	DL-7381S1-08-3024-P-C
				36°	DL-7381S1-08-3036-P-C
COB LED	8W	AC220-240V	4000K	15°	DL-7381S1-08-4015-P-C
				24°	DL-7381S1-08-4024-P-C
				36°	DL-7381S1-08-4036-P-C
COB LED	8W	AC220-240V	5000K	15°	DL-7381S1-08-5015-P-C
				24°	DL-7381S1-08-5024-P-C
				36°	DL-7381S1-08-5036-P-C

Power Supply: P (1-On / Off 2-Phase Dim 3-DALI Dim 4-1-10V Dim)


Colour Finish: C (WW-White / White BB-Black / Black)



Controller: On / Off, Dimmable, Dali

DIMENSION
unit:mm

DL-7381-08



DL-7381S1-08

