


FANO series

RECESSED (FIXED/ADJUSTABLE/FIXED) DOWNLIGHT



Light Source	Power	Voltage	CCT	Beam Angle	Code
COB LED	15W	AC220-240V	3000K	15°	DL-5222A-15-3015-P-C
				25°	DL-5222A-15-3025-P-C
				38°	DL-5222A-15-3038-P-C
COB LED	15W	AC220-240V	4000K	15°	DL-5222A-15-4015-P-C
				25°	DL-5222A-15-4025-P-C
				38°	DL-5222A-15-4038-P-C
COB LED	15W	AC220-240V	5000K	15°	DL-5222A-15-5015-P-C
				25°	DL-5222A-15-5025-P-C
				38°	DL-5222A-15-5038-P-C
COB LED	15W	AC220-240V	3000K	15°	DL-5222-15-3015-P-C
				25°	DL-5222-15-3025-P-C
				38°	DL-5222-15-3038-P-C
COB LED	15W	AC220-240V	4000K	15°	DL-5222-15-4015-P-C
				25°	DL-5222-15-4025-P-C
				38°	DL-5222-15-4038-P-C
COB LED	15W	AC220-240V	5000K	15°	DL-5222-15-5015-P-C
				25°	DL-5222-15-5025-P-C
				38°	DL-5222-15-5038-P-C

Power Supply: **P** (1-On / Off) **2**-Phase Dim **3**-DALI Dim **4**-1-10V Dim)


Colour Finish: **C** (WW-White / White) **BB**-Black / Black)



Controller: On / Off, Dimmable, Dali

DIMENSION
unit:mm


DL-5222A-15



— 082 —



DL-5222-15



— 082 —



FANO series

PRODUCT INTRODUCTION

Recessed LED downlight with quality aluminum body in powder-coated, with multiple reflecting angles of anti-dazzle reflector for selection, excellent heat sink capability, remote LED driver.

Application

Supermarket, chain store, shopping mall, villa, hotel, hall.



LOW GLARE DOWNLIGHT

LOW GLARE DOWNLIGHT

FANO series

RECESSED (FIXED/ADJUSTABLE) DOWNLIGHT



Light Source	Power	Voltage	CCT	Beam Angle	Code
COB LED	15W	AC220-240V	3000K	15°	DL-5224A-15-3015-P-C
				25°	DL-5224A-15-3025-P-C
				38°	DL-5224A-15-3038-P-C
COB LED	15W	AC220-240V	4000K	15°	DL-5224A-15-4015-P-C
				25°	DL-5224A-15-4025-P-C
				38°	DL-5224A-15-4038-P-C
COB LED	15W	AC220-240V	5000K	15°	DL-5224A-15-5015-P-C
				25°	DL-5224A-15-5025-P-C
				38°	DL-5224A-15-5038-P-C
COB LED	15W	AC220-240V	3000K	15°	DL-5224-15-3015-P-C
				25°	DL-5224-15-3025-P-C
				38°	DL-5224-15-3038-P-C
COB LED	15W	AC220-240V	4000K	15°	DL-5224-15-4015-P-C
				25°	DL-5224-15-4025-P-C
				38°	DL-5224-15-4038-P-C
COB LED	15W	AC220-240V	5000K	15°	DL-5224-15-5015-P-C
				25°	DL-5224-15-5025-P-C
				38°	DL-5224-15-5038-P-C

Power Supply: P (1-On / Off 2-Phase Dim 3-DALI Dim 4-1-10V Dim)



Colour Finish: C (WW-White / White BB-Black / Black)





Controller: On / Off, Dimmable, Dali

DIMENSION unit:mm

DL-5224A-15




DL-5224-15



FANO series

TRIMLESS (FIXED/ADJUSTABLE) DOWNLIGHT



Light Source	Power	Voltage	CCT	Beam Angle	Code
COB LED	15W	AC220-240V	3000K	15°	DL-5223A-15-3015-P-C
				25°	DL-5223A-15-3025-P-C
				38°	DL-5223A-15-3038-P-C
COB LED	15W	AC220-240V	4000K	15°	DL-5223A-15-4015-P-C
				25°	DL-5223A-15-4025-P-C
				38°	DL-5223A-15-4038-P-C
COB LED	15W	AC220-240V	5000K	15°	DL-5223A-15-5015-P-C
				25°	DL-5223A-15-5025-P-C
				38°	DL-5223A-15-5038-P-C
COB LED	15W	AC220-240V	3000K	15°	DL-5223-15-3015-P-C
				25°	DL-5223-15-3025-P-C
				38°	DL-5223-15-3038-P-C
COB LED	15W	AC220-240V	4000K	15°	DL-5223-15-4015-P-C
				25°	DL-5223-15-4025-P-C
				38°	DL-5223-15-4038-P-C
COB LED	15W	AC220-240V	5000K	15°	DL-5223-15-5015-P-C
				25°	DL-5223-15-5025-P-C
				38°	DL-5223-15-5038-P-C

Power Supply: P (1-On / Off 2-Phase Dim 3-DALI Dim 4-1-10V Dim)


Colour Finish: C (WW-White / White BB-Black / Black)



Controller: On / Off, Dimmable, Dali

DIMENSION unit:mm

DL-5223A-15



DL-5223-15

