

HERTZ series



PRODUCT INTRODUCTION

The top Aksu spray paint surface treatment of aviation aluminum is adopted, and the texture is delicate.

The curvature of the face ring is 12.8 degrees, which can be integrated with the ceiling, making its installation effect more beautiful.

Shift structure, 0-6mm precise dimming and light control to achieve the best lighting effect.


The anti-glare depth reaches 7.5 depth, achieving the effect of seeing the light without seeing the light, Rinio optical principle.

Uses the principle of breathing dynamics of the Politecnico di Milano air convection radiator.



HERTZ series

RECESSED ADJUSTABLE DOWNLIGHT



Light Source	Power	Voltage	CCT	Beam Angle	Code
COB LED	7W	AC220-240V	3000K	15°	DL-HZ01-55-07-3015-P-C
				24°	DL-HZ01-55-07-3024-P-C
				36°	DL-HZ01-55-07-3036-P-C
COB LED	7W	AC220-240V	4000K	15°	DL-HZ01-55-07-4015-P-C
				24°	DL-HZ01-55-07-4024-P-C
				36°	DL-HZ01-55-07-4036-P-C
COB LED	7W	AC220-240V	5000K	15°	DL-HZ01-55-07-5015-P-C
				24°	DL-HZ01-55-07-5024-P-C
				36°	DL-HZ01-55-07-5036-P-C
COB LED	10W	AC220-240V	3000K	15°	DL-HZ01-75-10-3015-P-C
				24°	DL-HZ01-75-10-3024-P-C
				36°	DL-HZ01-75-10-3036-P-C
COB LED	10W	AC220-240V	4000K	15°	DL-HZ01-75-10-4015-P-C
				24°	DL-HZ01-75-10-4024-P-C
				36°	DL-HZ01-75-10-4036-P-C
COB LED	10W	AC220-240V	5000K	15°	DL-HZ01-75-10-5015-P-C
				24°	DL-HZ01-75-10-5024-P-C
				36°	DL-HZ01-75-10-5036-P-C
COB LED	15W	AC220-240V	3000K	15°	DL-HZ01-95-15-3015-P-C
				24°	DL-HZ01-95-15-3024-P-C
				36°	DL-HZ01-95-15-3036-P-C
COB LED	15W	AC220-240V	4000K	15°	DL-HZ01-95-15-4015-P-C
				24°	DL-HZ01-95-15-4024-P-C
				36°	DL-HZ01-95-15-4036-P-C
COB LED	15W	AC220-240V	5000K	15°	DL-HZ01-95-15-5015-P-C
				24°	DL-HZ01-95-15-5024-P-C
				36°	DL-HZ01-95-15-5036-P-C

Power Supply: P (1-On / Off 2-Phase Dim 3-DALI Dim 4-1-10V Dim)



Colour Finish: C (WM-White / Matte Silver WG-Gloss Silver WO-White / Orange WR-White / Rose Gold WC-White / Gold)





Controller: On / Off, Dimmable, Dali

DIMENSION unit:mm


DL-HZ01-55-07



DL-HZ01-75-10




DL-HZ01-95-15



NEMO series

TRIMLESS ADJUSTABLE DOWNLIGHT



Light Source	Power	Voltage	CCT	Beam Angle	Code
COB LED	7W	AC220-240V	3000K	15°	DL-HZ02-55-07-3015-P-C
				24°	DL-HZ02-55-07-3024-P-C
				36°	DL-HZ02-55-07-3036-P-C
COB LED	7W	AC220-240V	4000K	15°	DL-HZ02-55-07-4015-P-C
				24°	DL-HZ02-55-07-4024-P-C
				36°	DL-HZ02-55-07-4036-P-C
COB LED	7W	AC220-240V	5000K	15°	DL-HZ02-55-07-5015-P-C
				24°	DL-HZ02-55-07-5024-P-C
				36°	DL-HZ02-55-07-5036-P-C
COB LED	10W	AC220-240V	3000K	15°	DL-HZ02-75-10-3015-P-C
				24°	DL-HZ02-75-10-3024-P-C
				36°	DL-HZ02-75-10-3036-P-C
COB LED	10W	AC220-240V	4000K	15°	DL-HZ02-75-10-4015-P-C
				24°	DL-HZ02-75-10-4024-P-C
				36°	DL-HZ02-75-10-4036-P-C
COB LED	10W	AC220-240V	5000K	15°	DL-HZ02-75-10-5015-P-C
				24°	DL-HZ02-75-10-5024-P-C
				36°	DL-HZ02-75-10-5036-P-C
COB LED	15W	AC220-240V	3000K	15°	DL-HZ02-95-15-3015-P-C
				24°	DL-HZ02-95-15-3024-P-C
				36°	DL-HZ02-95-15-3036-P-C
COB LED	15W	AC220-240V	4000K	15°	DL-HZ02-95-15-4015-P-C
				24°	DL-HZ02-95-15-4024-P-C
				36°	DL-HZ02-95-15-4036-P-C
COB LED	15W	AC220-240V	5000K	15°	DL-HZ02-95-15-5015-P-C
				24°	DL-HZ02-95-15-5024-P-C
				36°	DL-HZ02-95-15-5036-P-C

Power Supply: P (1-On / Off 2-Phase Dim 3-DALI Dim 4-1-10V Dim)



Colour Finish: C (WM-White / Matte Silver WG-Gloss Silver WO-White / Orange WR-White / Rose Gold WC-White / Gold)





Controller: On / Off, Dimmable, Dali

DIMENSION unit:mm

DL-HZ02-55-07



DL-HZ02-75-10



DL-HZ02-95-15

