

MINI DOWNLIGHT



NICO series

PRODUCT INTRODUCTION

Minimalism and simplicity are the key words to describe collection. coming directly from the ceiling, slim lighting design, narrow beam angle, just 10 °, most dramatic lighting effects can be created through the high contrast between dark and light. trim and trimless version, Different spaces and different functions. However, the building will be mostly used to hotel areas.

NICO series

RECESSED DOWNLIGHT



Light Source	Power	Voltage	CCT	Beam Angle	Code
COB LED	6W	AC220-240V	3000K	10°	DL-1090-06-3010-P-C
				15°	DL-1090-06-3015-P-C
				24°	DL-1090-06-3024-P-C
COB LED	6W	AC220-240V	4000K	10°	DL-1090-06-4010-P-C
				15°	DL-1090-06-4015-P-C
				24°	DL-1090-06-4024-P-C
COB LED	6W	AC220-240V	5000K	10°	DL-1090-06-5010-P-C
				15°	DL-1090-06-5015-P-C
				24°	DL-1090-06-5024-P-C
COB LED	6W	AC220-240V	3000K	10°	DL-1090A-06-3010-P-C
				15°	DL-1090A-06-3015-P-C
				24°	DL-1090A-06-3024-P-C
COB LED	6W	AC220-240V	4000K	10°	DL-1090A-06-4010-P-C
				15°	DL-1090A-06-4015-P-C
				24°	DL-1090A-06-4024-P-C
COB LED	6W	AC220-240V	5000K	10°	DL-1090A-06-5010-P-C
				15°	DL-1090A-06-5015-P-C
				24°	DL-1090A-06-5024-P-C

Power Supply: **P** (1-On / Off 2-Phase Dim 3-DALI Dim 4-1-10V Dim)


Colour Finish: **C** (WW-White / White BB-Black / Black WB-White / Black WD-White / Dark Light BW-Black / White
WS-White / Silver BS-Black / Silver)





Controller: On / Off, Dimmable, Dali

DIMENSION
unit:mm

DL-1090-06



DL-1090A-06



NICO series


PRODUCT INTRODUCTION

In this typology of products, not only a high technical performance of the luminaires is required, but also a decorative elegance, which is vital.



NICO series

RECESSED FIXED DOWNLIGHT



Light Source	Power	Voltage	CCT	Beam Angle	Code
COB LED	9W	AC220-240V	3000K	15°	DL-1091-09-3015-P-C
				24°	DL-1091-09-3024-P-C
				36°	DL-1091-09-3036-P-C
				50°	DL-1091-09-3050-P-C
COB LED	9W	AC220-240V	4000K	15°	DL-1091-09-4015-P-C
				24°	DL-1091-09-4024-P-C
				36°	DL-1091-09-4036-P-C
				50°	DL-1091-09-4050-P-C
COB LED	9W	AC220-240V	5000K	15°	DL-1091-09-5015-P-C
				24°	DL-1091-09-5024-P-C
				36°	DL-1091-09-5036-P-C
				50°	DL-1091-09-5050-P-C
COB LED	15W	AC220-240V	3000K	15°	DL-1094-15-3015-P-C
				24°	DL-1094-15-3024-P-C
				36°	DL-1094-15-3036-P-C
				50°	DL-1094-15-3050-P-C
COB LED	15W	AC220-240V	4000K	15°	DL-1094-15-4015-P-C
				24°	DL-1094-15-4024-P-C
				36°	DL-1094-15-4036-P-C
				50°	DL-1094-15-4050-P-C
COB LED	15W	AC220-240V	5000K	15°	DL-1094-15-5015-P-C
				24°	DL-1094-15-5024-P-C
				36°	DL-1094-15-5036-P-C
				50°	DL-1094-15-5050-P-C

Power Supply: P (1-On / Off 2-Phase Dim 3-DALI Dim 4-1-10V Dim)


Colour Finish: C (WW-White / White BB-Black / Black WB-White / Black WD-White / Dark Light BW-Black / White WS-White / Silver BS-Black / Silver)




Controller: On / Off, Dimmable, Dali

DIMENSION unit:mm

DL-1091-09




DL-1094-15



NICO series

RECESSED ADJUSTABLE DOWNLIGHT



Light Source	Power	Voltage	CCT	Beam Angle	Code
COB LED	9W	AC220-240V	3000K	15°	DL-1091A-09-3015-P-C
				24°	DL-1091A-09-3024-P-C
				36°	DL-1091A-09-3036-P-C
				50°	DL-1091A-09-3050-P-C
COB LED	9W	AC220-240V	4000K	15°	DL-1091A-09-4015-P-C
				24°	DL-1091A-09-4024-P-C
				36°	DL-1091A-09-4036-P-C
				50°	DL-1091A-09-4050-P-C
COB LED	9W	AC220-240V	5000K	15°	DL-1091A-09-5015-P-C
				24°	DL-1091A-09-5024-P-C
				36°	DL-1091A-09-5036-P-C
				50°	DL-1091A-09-5050-P-C
COB LED	15W	AC220-240V	3000K	15°	DL-1094A-15-3015-P-C
				24°	DL-1094A-15-3024-P-C
				36°	DL-1094A-15-3036-P-C
				50°	DL-1094A-15-3050-P-C
COB LED	15W	AC220-240V	4000K	15°	DL-1094A-15-4015-P-C
				24°	DL-1094A-15-4024-P-C
				36°	DL-1094A-15-4036-P-C
				50°	DL-1094A-15-4050-P-C
COB LED	15W	AC220-240V	5000K	15°	DL-1094A-15-5015-P-C
				24°	DL-1094A-15-5024-P-C
				36°	DL-1094A-15-5036-P-C
				50°	DL-1094A-15-5050-P-C

Power Supply: P (1-On / Off 2-Phase Dim 3-DALI Dim 4-1-10V Dim)


Colour Finish: C (WW-White / White BB-Black / Black WB-White / Black WD-White / Dark Light BW-Black / White WS-White / Silver BS-Black / Silver)




Controller: On / Off, Dimmable, Dali

DIMENSION unit:mm

DL-1091A-09




DL-1094A-15



NICO series

TRIMLESS FIXED DOWNLIGHT



Light Source	Power	Voltage	CCT	Beam Angle	Code
COB LED	9W	AC220-240V	3000K	15°	DL-1092-09-3015-P-C
				24°	DL-1092-09-3024-P-C
				36°	DL-1092-09-3036-P-C
				50°	DL-1092-09-3050-P-C
COB LED	9W	AC220-240V	4000K	15°	DL-1092-09-4015-P-C
				24°	DL-1092-09-4024-P-C
				36°	DL-1092-09-4036-P-C
				50°	DL-1092-09-4050-P-C
COB LED	9W	AC220-240V	5000K	15°	DL-1092-09-5015-P-C
				24°	DL-1092-09-5024-P-C
				36°	DL-1092-09-5036-P-C
				50°	DL-1092-09-5050-P-C
COB LED	15W	AC220-240V	3000K	15°	DL-1093-15-3015-P-C
				24°	DL-1093-15-3024-P-C
				36°	DL-1093-15-3036-P-C
				50°	DL-1093-15-3050-P-C
COB LED	15W	AC220-240V	4000K	15°	DL-1093-15-4015-P-C
				24°	DL-1093-15-4024-P-C
				36°	DL-1093-15-4036-P-C
				50°	DL-1093-15-4050-P-C
COB LED	15W	AC220-240V	5000K	15°	DL-1093-15-5015-P-C
				24°	DL-1093-15-5024-P-C
				36°	DL-1093-15-5036-P-C
				50°	DL-1093-15-5050-P-C

Power Supply: P (1-On / Off 2-Phase Dim 3-DALI Dim 4-1-10V Dim)



Colour Finish: C (WW-White / White BB-Black / Black WB-White / Black WD-White / Dark Light BW-Black / White WS-White / Silver BS-Black / Silver)




Controller: On / Off, Dimmable, Dali

DIMENSION unit:mm

DL-1092-09




DL-1093-15



NICO series

TRIMLESS ADJUSTABLE DOWNLIGHT



Light Source	Power	Voltage	CCT	Beam Angle	Code
COB LED	9W	AC220-240V	3000K	15°	DL-1092A-09-3015-P-C
				24°	DL-1092A-09-3024-P-C
				36°	DL-1092A-09-3036-P-C
				50°	DL-1092A-09-3050-P-C
COB LED	9W	AC220-240V	4000K	15°	DL-1092A-09-4015-P-C
				24°	DL-1092A-09-4024-P-C
				36°	DL-1092A-09-4036-P-C
				50°	DL-1092A-09-4050-P-C
COB LED	9W	AC220-240V	5000K	15°	DL-1092A-09-5015-P-C
				24°	DL-1092A-09-5024-P-C
				36°	DL-1092A-09-5036-P-C
				50°	DL-1092A-09-5050-P-C
COB LED	15W	AC220-240V	3000K	15°	DL-1093A-15-3015-P-C
				24°	DL-1093A-15-3024-P-C
				36°	DL-1093A-15-3036-P-C
				50°	DL-1093A-15-3050-P-C
COB LED	15W	AC220-240V	4000K	15°	DL-1093A-15-4015-P-C
				24°	DL-1093A-15-4024-P-C
				36°	DL-1093A-15-4036-P-C
				50°	DL-1093A-15-4050-P-C
COB LED	15W	AC220-240V	5000K	15°	DL-1093A-15-5015-P-C
				24°	DL-1093A-15-5024-P-C
				36°	DL-1093A-15-5036-P-C
				50°	DL-1093A-15-5050-P-C

Power Supply: P (1-On / Off 2-Phase Dim 3-DALI Dim 4-1-10V Dim)



Colour Finish: C (WW-White / White BB-Black / Black WB-White / Black WD-White / Dark Light BW-Black / White WS-White / Silver BS-Black / Silver)



Controller: On / Off, Dimmable, Dali

DIMENSION unit:mm

DL-1092A-09



DL-1093A-15

