


**SCOTT** series

SURFACE DOWNLIGHT



Light Source	Power	Voltage	CCT	Beam Angle	Code
COB LED	12W	AC220-240V	3000K	30° 45°	DL-3061-12-3030-P-C DL-3061-12-3045-P-C
COB LED	12W	AC220-240V	4000K	30° 45°	DL-3061-12-4030-P-C DL-3061-12-4045-P-C
COB LED	12W	AC220-240V	5000K	30° 45°	DL-3061-12-5030-P-C DL-3061-12-5045-P-C
COB LED	17W	AC220-240V	3000K	30° 45°	DL-3062-17-3030-P-C DL-3062-17-3045-P-C
COB LED	17W	AC220-240V	4000K	30° 45°	DL-3062-17-4030-P-C DL-3062-17-4045-P-C
COB LED	17W	AC220-240V	5000K	30° 45°	DL-3062-17-5030-P-C DL-3062-17-5045-P-C

Power Supply: P (1-On / Off 2-Phase Dim 3-DALI Dim 4-1-10V Dim)


Colour Finish: C (WW-White / White BB-Black / Black WB-White / Black)




Controller: On / Off, Dimmable, Dali

DIMENSION  
unit:mm

DL-3061-12



DL-3062-17



**SCOTT** series

IP65 WEATHER RESISTANCE

its model with IP65 rate weather resistance, the use of refraction instead of reflection to direct the light outwards from the piece manages to extraordinarily diminish the glare and achieves light concentration at a well defined angle.

